

X340+ Bright and portable



- Bright XGA projector 3600 ANSI lumens
- Easy connectivity HDMI, VGA, USB-A Power, 2W speaker
- Low ownership costs up to 15,000 hours² lamp life
- Lightweight and portable

Project your presentations effortlessly any time on day with the bright X340+. Designed for meeting rooms and classrooms, this small projector boasts high brightness, long lamp life and energy-saving features to provide you with a low overall cost of ownership.

This projector is easy to connect to with multiple inputs, a built-in speaker and USB Power. Perfect for connecting HDMI dongles such as the Google Chromecast and the Optoma HDCast Pro (sold separately) or a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight projector can be installed or taken on the move for off-site meetings with the optional carry bag (sold separately).

Specifications

Display/image	
Display technology	
Resolution	XGA (1024x768)
Brightness	3,600 lumens
Contrast ratio	22,000:1
Native aspect ratio	4:3
Aspect ratio - compatible	16:9, 16:10
Keystone correction - vertical	40
Horizontal scan rate	15.3 ~ 91.1Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	75%
Screen size	0.71m - 7.73m (27.78in - 304.4in)(Diagonal)
Lamp info	
Light source	Lamp
Lamp watts	195
Lamp life (hours)	5000 (Bright), 7000 (Dynamic), 6000 (Eco), 8000 (Eco+), 15000 (Education)
Lamp life (education)	15,000 hours
Optical	10,000 10010
Optical Throw ratio	1.94:1 - 2.16:1
Projection distance (m)	1.2m - 12m
Zoom	1.1
Zoom type	Manual
Focal length (mm)	21.85 ~ 24.01
Native offset	115%
Connectivity	110/0
Connections	
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm
	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x
General	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A
	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232
General Noise level (typical) PC compatibility	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB
Noise level (typical) PC compatibility	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Noise level (typical) PC compatibility	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N,
	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Noise level (typical) PC compatibility	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480//p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
Noise level (typical) PC compatibility 2D compatibility	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p,
Noise level (typical) PC compatibility 2D compatibility 3D compatibility	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:
Noise level (typical) PC compatibility 2D compatibility	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080(50/60Hz), 1080(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian,
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese,
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MJ, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish,
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MJ, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count	 Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bax, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080(50/60Hz), Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 2W
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box	 Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bax, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power	 Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MJ, 3.58MHz, 4.43MHz PAL B/D/G/H/I/MN, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 2W AC power cord, remote control, Battery, basic user manual
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power Power supply	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UKGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MJ, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 2W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply Power consumption	 Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MJ, 3.58MHz, 4.43MHz PAL B/D/G/H/I/MN, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 2W AC power cord, remote control, Battery, basic user manual
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power Power consumption (standby)	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/W/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480%, 576%, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 2W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz 0.5W
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power consumption (standby) Power consumption (min)	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/W/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480//p, 576i/p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 2W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz 0.5W 187W
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power consumption (standby) Power consumption (min) Power consumption (max)	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/W/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480%, 576%, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 2W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz 0.5W
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power Power consumption (standby) Power consumption (min) Power consumption (max)	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///WN, 4,43MHz SECAM B/D/G/K//K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 2W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz 0.5W 187W 225W
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/W/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480//p, 576i/p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 2W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz 0.5W 187W





Copyright © 2018, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 22102018112348