

S342e

Bright projection









- Bright SVGA projector 3700 ANSI lumens
- Easy connectivity HDMI, VGA, USB Power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Project bright vibrant presentations effortlessly any time of day. Designed for meeting rooms and classrooms, the S342e boasts amazing colour, long lamp life and energy-saving features to provide you with a low overall cost of ownership.



Specifications

EAN: 5055387661196, Colour: Black

Display/image Display technology DIPTM Resolution SVGA (800x600) 3,700 lumens Brightness Contrast ratio 22,000:1 Native aspect ratio 4.3 Aspect ratio - compatible 16:9 Keystone correction - vertical +/-40° Horizontal scan rate 15.38 ~ 91.15Khz 50 ~ 85(120 for 3D)Hz Vertical scan rate Uniformity 75%

Screen size 0.71m ~ 7.73m (27.78" ~ 304.4") diagonal

Lamp info Light source type Lamp Lamp watts 203 6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+) Lamp life hours (up to)

Optical 1.94:1 ~ 2.16:1 Throw ratio Projection distance (m) 1m - 12m 1.1 Zoom Zoom type Manual Focal length (mm) 21.85 ~ 24 115% Native offset

Connectivity Connections

3D

Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1

x Composite video, 1 x Audio 3.5mm

Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A

Control 1 x RS232

General Noise level (typical) 27dB Noise level (max) 29dB

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

3D ready

Security Security bar, Kensington Lock, Password protected interface

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Tinnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style Remote control

Speaker count Watts per speaker 10W In the box AC power cord Remote control

Battery Basic user manual

HDCast Pro, QuickCast Bundle, WHD200 Optional wireless models

Power Power supply

100 ~ 240V, 50 ~ 60Hz

Power consumption (standby) 0.5W Power consumption (min) 187W Power consumption (max) 225W Weight and dimensions

Dimensions (W x D x H) mm 316 x 244 x 108 Gross weight 3.52 kg Net weight 3 kg





