

UHD35STx

Short throw 4K UHD gaming and home entertainment projector



- **Incredible True 4K UHD resolution visual experience - Perfect for big screen home entertainment and immersive gaming**
- **Short throw projection - Supersized 100" image from just over a few feet away**
- **Lights on viewing - Bright 3600 lumens**
- **Created for a competitive gaming advantage - Supports 1080p 240Hz at 4.2ms and 4K 60Hz at 16.9ms**



Immerse yourself in a world of Ultra HD gaming, live sports and TV shows. The UHD35STx delivers impressive bright 4K UHD high-quality images, lightning-fast input lag as low as 4.2ms and a high refresh rate of 240Hz - perfect for a competitive gaming advantage.

Featuring a short throw lens, it can be placed just a few feet away from the projection area while creating a supersized 100" image.

Specifications

UPC: 796435814533 , EAN: 5055387666443, Colour: White

| | |
|----------------------------------|---|
| Display/image | |
| Display technology | DLP™ |
| Resolution | UHD (3840x2160) |
| Brightness | 3,600 lumens |
| Contrast ratio | 1,000,000:1 |
| Native aspect ratio | 16:9 |
| Aspect ratio - compatible | 4:3 |
| Keystone correction - horizontal | +/-40° |
| Keystone correction - vertical | +/-40° |
| Horizontal scan rate | 31 ~ 135Khz |
| Vertical scan rate | 24 ~ 120Hz |
| Uniformity | 80% |
| Screen size | 36.43" ~ 300.53" diagonal |
| Lamp info | |
| Light source type | Lamp |
| Lamp watts | 240 |
| Lamp life hours (up to) | 4000 (Bright), 15000 (Dynamic), 10000 (Eco) |
| Optical | |
| Throw ratio | 0.5:1 |
| Projection distance | 15.75" - 129.92" |
| Zoom | 1 |
| Zoom type | Fixed |
| Focal length (mm) | 7.51mm |
| Lens shift | Vertical +0% |
| Native offset | 116% |
| Connectivity | |
| Connections | Inputs 2 x HDMI 2.0 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power 1.5A Control 1 x RS232, 1 x 12V trigger |
| General | |
| Noise level (min) | 24dB |
| Noise level (max) | 28dB |
| PC compatibility | UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| 2D compatibility | 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) |
| 3D compatibility | Frame-pack: 1080p24, 720p50 / 60 |
| 3D | Full 3D |
| Security | Security bar, Kensington Lock, Password protected interface |
| OSD / display languages | 9 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish |
| Operating conditions | 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% |
| Remote control | Backlit home remote |
| Speaker count | 1 |
| Watts per speaker | 10W |
| In the box | AC power cord Remote control 2x AAA batteries Basic user manual |
| Input lag | 4.00ms |
| Power | |
| Power supply | 100 ~ 240V, 50 ~ 60Hz |
| Power consumption (standby) | 0.5W |
| Power consumption (min) | 220W |
| Power consumption (max) | 320W |
| Weight and dimensions | |
| Dimensions (W x D x H) | 12.4" x 10.63" x 4.65" |
| Gross weight | 10.32 lbs |
| Net weight | 7.72 lbs |

