

# FHD26528

Fully optimised HD LED display – 5 x 2.8m (226" diagonal)



- **High calibre, high-resolution indoor Full HD LED display**
- **Easy installation and maintenance - surface mount and front access**
- **Ultra-thin panel depth - discreet, space-saving design**
- **Best in class processing and switching - HQUltra technology**

Optoma is the one-stop solution provider for projection and LED displays with its range of 4K UHD, Full HD and custom LED displays.

The ultra-thin, 16:9 native aspect ratio Full HD LED displays blend discretely into any corporate, higher education, hospitality and digital signage environment.

Easy to install, operate and maintain, they are designed for ultimate reliability and superior image quality.



# Specifications

<b>Screen</b>	
Screen resolution	1080p Full HD (1920x1080)
Screen size (diagonal)	226"
Screen size	5000 x 2812.5
Minimum viewing distance	2.6m
Brightness (before calibration)	800 nits
Brightness (after calibration)	800 nits
Contrast	4000:1
Dimensions (W x D x H) mm	5000 x 54 x 2812.5
<b>Screen processing</b>	
Scaler-switcher	LS200T
Sender	MCTRL660
<b>LEDs</b>	
Pixel pitch (H x V)	2.604mm
LEDs per pixel	1R1G1B
Red wavelength (dominant)	620nm
Green wavelength (dominant)	520nm
Blue wavelength (dominant)	465nm
<b>Pixels</b>	
Pixel configuration	SMD 3-1
LED face colour	Black
LED size	SMD2020
Pixel resolution (width)	192 pixels/module
Pixel resolution (height)	108 pixels/module
Pixels per area	147,456 pixels/m <sup>2</sup>
<b>Module</b>	
Active module width	5,000mm
Active module height	2812.5mm
Standard active module area	0.1406m <sup>2</sup>
Viewing angle - horizontal	>160°
Viewing angle - vertical	>160°
Ingress protection (front)	IP43
Ingress protection (back)	IP21
LED fixings	Front access
Storage temperature range	-10 - +50°C
Operating conditions	10 - 90 non-condensing
Operating temperature (min)	-10°C
Operating temperature (max)	50°C
<b>Colour</b>	
Greyscale processing depth	16 bits
Number of colours	281 (trillions)
Refresh rate	>3840 Hz
<b>Brightness</b>	
Brightness (before calibration)	800nits
Brightness (after calibration)	800nits
Contrast ratio	4,000
Brightness control levels	256
<b>Power</b>	
Input power (max)	72watts per panel
Power supply	110-240
<b>Other</b>	
Mechanical alignment adjustment	x/y/z (x/y/z planes)
Mitering	-90°
Mounting frame	Optional
<b>Connectivity</b>	
Connections	<b>Inputs</b> 2 x HDMI UHD 4K, 1 x HDMI FHD 1080P, 1 x DVI/HDMI, 1 x HDBaseT 4K, 1 x DisplayPort 4K, 1 x Component input via DVI-U, 1 x Composite video, 2 x 3G-SDI, 1 x VGA, 1 x RJ45 streaming, 2 x Microphone, 6 x Stereo analogue audio <b>Outputs</b> 1 x DVI/HDMI, 1 x HDMI UHD 4K, 1 x HDBaseT 4K, 1 x Speaker <b>Control</b> 1 x RS232, 1 x RJ45