

X341+ Bright and portable



- Bright XGA projector 3600 ANSI lumens
- Easy connectivity HDMI, VGA, USB-A Power, 2W speaker
- Low ownership costs up to 15,000 hours<sup>2</sup> lamp life
- Lightweight and portable

Project your presentations effortlessly any time on day with the bright X341+. Designed for meeting rooms and classrooms, this small projector boasts high brightness, long lamp life and energy-saving features to provide you with a low overall cost of ownership.

This projector is easy to connect to with multiple inputs, a built-in speaker and USB Power. Perfect for connecting HDMI dongles such as the Google Chromecast and the Optoma HDCast Pro (sold separately) or a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight projector can be installed or taken on the move for off-site meetings with the optional carry bag (sold separately).

## **Specifications**

•		
Display/image		
Display technology	DLP	
Resolution	XGA (1024x768)	
Brightness	3,600 lumens	
Contrast ratio	25,000:1	
Native aspect ratio	4:3	
Aspect ratio - compatible	16:9,16:10	
Keystone correction - vertical	+/-40°	HOM WIA WIGHD
Horizontal scan rate	15.3 ~ 91.1Khz	٠ 🛞 🕲
Vertical scan rate	24 ~ 85(120 for 3D)Hz	Optomo
Uniformity	75%	
Screen size	0.71m - 7.73m (27.78in - 304.4in)	
Lamp info		
Light source type	Lamp	
Lamp watts	195	
Lamp life (hours)	5000 (Bright), 7000 (Dynamic), 6000 (Eco), 8000 (Eco+),	
Lump no (nouro)	15000 (Education)	
Lamp life (education)	15,000 hours	
Optical		
Throw ratio	1.94:1 - 2.16:1	
Projection distance (m)	1.2m - 12m	
Zoom	1.1	
Zoom type	Manual	
Focal length (mm)	21.85 ~ 24.01	
Native offset	115%	
Connectivity		
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB),	
	1 x Composite video, 1 x Audio 3.5mm	
	Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x	
	USB-A power 1A Control 1 x RS232	
	CONTROL 1 X R3232	
General		
Noise level (typical)	29dB	
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac	
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N,	
	4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p,	
3D compatibility	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:	
SD compatibility	1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60	
3D	Full 3D	
Security	Security bar, Kensington Lock, Password protected interface	
OSD / display languages	25 languages:	
cob / alopiay languages		an,Greek,Hungarian,Indonesian,Italian,Japanese,Norwegian,Polish,Portuguese,Romanian
	(simplified),Spanish,Swedish,Chinese	
	(traditional),Turkish,Vietnamese	
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m	
Remote control	Card style	
Speaker count	1	
Watts per speaker	2W	
In the box	AC power cord, remote control, Battery, basic user manual	
Power		
Power supply	100 ~ 240V, 50 ~ 60Hz	
Power consumption	0.5W	
(standby)		
Power consumption (min)	187W	
Power consumption (max)	225W	
Wainha and dimensions		
•		
Weight and dimensions Net weight	2.17kg	
•	2.17kg 298 x 230 x 965	

Copyright © 2018, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 06122018102848